

TROLLEYS & BEAM CLAMPS

ET-A Trolley

COFFING ET-A Model - The economical choice for most commercial and light-duty industrial applications. The ET-A can be modified to fit a variety of beam styles and sizes, up to an 8" flange width.



1/4 - 5 Ton
Made in USA

- **CAPACITIES** - Rated loads from 1/4 to 5 Tons.
- **ECONOMICAL** - Excellent low cost choice for most manual and light-duty powered applications
- **UNIVERSAL HANGING CLEVIS** - Accepts all Coffing hook-mounted hoists.
- **ADJUSTABLE** - Trolley is easily adjusted to fit any tapered or flat beam flange within range of adjustment, up to an 8" flange width.
- **WRAP-AROUND SIDE PLATES** - Act as safety lugs to increase operator safety and act as bumpers to protect wheels.
- **DUAL TREAD WHEELS** - Cast iron wheels fit any tapered or flat beam flange within range of adjustment. Wheels include permanently lubricated, shielded ball bearings for long life and low maintenance.
- **OPTIONS** - Adapter lugs available for mounting EC and ELC hoists.
- **LIFETIME WARRANTY**

S P E C I F I C A T I O N S

ET-A Trolleys

Capacity		Model Number	Standard Beam Height (In.)	I-Beam Width (In.)	Minimum Radius Curve (In.) †	Wheel Tread Diameter (In.)	Net Weight (Lbs.)
Lbs.	Tons						
500	1/4	ET-05-A	4-10	2.66-8.045	36	2 1/4	14
1000	1/2	ET-10-A	4-10	2.66-8.045	36	2 1/4	14
2000	1	ET-20-A	5-12	3.00-8.045	48	2 3/4	23
3000	1 1/2	ET-30-A	6-18	3.33-8.045	60	4 1/4	52
4000	2	ET-40-A	6-18	3.33-8.045	60	4 1/4	52
6000	3	ET-60-A	8-20	4.00-8.045	60	4 1/4	60
10000	5	ET-100-A	10-24	4.60-8.05	60	4 3/8	96

NOTE:
For complete dimensional data, refer to Coffing Dimensional Databook.

† Minimum recommended radius for best wheel life.