

CY Trolley

COFFING CY Model - Designed to meet all your heavy lifting needs. The CY can be adapted for a variety of beam sizes and styles, and can be equipped with spark resistant features. The CY is recommended for heavy-duty industrial applications.

- **CAPACITIES** - Rated loads from 4-40 Tons in plain and geared models. Geared trolleys have standard 7-foot hand chain drop.
- **RUGGED** - Designed for heavy-duty industrial applications.
- **HANGING CLEVIS** - Accepts all Coffing hook-mounted hoists. Steel equalizing pin can be used to suspend hoist for low headroom applications.
- **ADJUSTABLE** - Fits a wide range of beam sizes.
- **SIDE PLATES WITH SAFETY LUGS** - Act as safety lugs to increase operator safety and act as bumpers to protect wheels.
- **BALL TREAD WHEELS** - Fully machined forged steel wheels (4-6 Ton models) or cast iron wheels (8-20 Ton models) fit any tapered or flat beam flange within range of adjustment. Each wheel has two lifetime lubricated, sealed tapered roller bearings for long life and low maintenance.
- **OPTIONS** - Wide flange and patented track models available. Spark resistant units available in 4 to 8 Ton models.
- **LIFETIME WARRANTY**



4 - 40 Ton
Made in USA

SPECIFICATIONS

CY Trolleys — Plain & Geared

Capacity		Model Number *	Beam Height (In.)	I-Beam Width (In.)	Minimum Radius Curve (In.)	Net Weight	
Lbs.	Tons					Plain (Lbs.)	Geared (Lbs.)
8000	4	CY-80P(G)	8-24	4.00-7.00	60	138	175
10000	5	CY-100P(G)	8-24	4.00-7.00	60	140	180
12000	6	CY-120P(G)	8-24	4.00-7.00	60	140	180
16000	8	CY-160P(G)	10-24	4.66-7.00	72	255	295
20000	10	CY-200P(G)	10-24	4.66-7.00	72	274	310
24000	12	CY-240P(G)	10-24	4.66-7.00	72	278	320
32000	16	CY-320P(G)	18-24	6.00-8.00	96	800	840
40000	20	CY-400P(G)	18-24	6.00-8.00	96	810	850
50000	25	CY-500P(G)	24	7.00-8.00	**	760	800
60000	30	CY-600P(G)	24	7.00-8.00	**	2,030	2,070
80000	40	CY-800P(G)	24	7.00-8.00	**	2,060	2,100

NOTE:

For complete dimensional data, refer to Coffing Dimensional Databook.

* When ordering, specify "P" for plain trolley or "G" for geared trolley.

** Contact us.

