

Stamped Steel — Versatile Performer

LSB-A Ratchet Lever Hoist

COFFING LSB-A Model - Stamped steel ratchet lever hoists are lightweight and durable. The LSB-A's low handle effort and 360° rotating handle make it easy to operate, and the one-handed free chaining mechanism provides easy rigging. The LSB-A is ideal for construction and commercial applications.

- **CAPACITIES & LIFT** - Rated loads of 3/4, 1 1/2, 3, and 6 Tons, with 5, 10, 15, and 20 foot standard lifts. Other lifts available.
- **RUGGED AND LIGHTWEIGHT** - Impact resistant stamped steel housing withstands rigorous use. Compact design is portable and easy to rig.
- **LOW HANDLE EFFORT** - Double reduction gearing and short handle with cushioned grip provide easy operation with minimal handle effort.
- **360° ROTATING HANDLE** - Provides versatile rigging options when used in confined spaces.
- **EASY FREE CHAINING** - State-of-the-art free wheeling mechanism allows quick and easy one-handed take-up and positioning of slack chain. Unconditional lifetime warranty on free-chain knob.
- **POSITIVE LOAD CONTROL** - Enclosed screw-and-disc type load brake stays clean and dry for positive load positioning. Safety latches on hooks for positive load engagement.
- **LONGER CHAIN LIFE** - Through-hardened load chain provides high strength and resists wear.
- **LIFETIME WARRANTY**



3/4 - 6 Ton

SPECIFICATIONS

LSB-A Ratchet Lever Hoists

Capacity		Model Number	Lift (Ft.) *	Strands of Load Chain	Minimum Distance Between Hooks (In.)	Handle Length (In.)	Average Handle Effort (Lbs.)	Net Weight (Lbs.)
Lbs.	Tons							
1500	3/4	LSB-1500A-5	5	1	11 ⁵ / ₈	9 ¹ / ₄	46	13
1500	3/4	LSB-1500A-10	10	1	11 ⁵ / ₈	9 ¹ / ₄	46	15
1500	3/4	LSB-1500A-15	15	1	11 ⁵ / ₈	9 ¹ / ₄	46	17
1500	3/4	LSB-1500A-20	20	1	11 ⁵ / ₈	9 ¹ / ₄	46	19
3000	1 1/2	LSB-3000A-5	5	1	14 ³¹ / ₃₂	13 ³ / ₄	55	22
3000	1 1/2	LSB-3000A-10	10	1	14 ³¹ / ₃₂	13 ³ / ₄	55	25
3000	1 1/2	LSB-3000A-15	15	1	14 ³¹ / ₃₂	13 ³ / ₄	55	28
3000	1 1/2	LSB-3000A-20	20	1	14 ³¹ / ₃₂	13 ³ / ₄	55	31
6000	3	LSB-6000A-5	5	1	16 ⁹ / ₁₆	13 ³ / ₄	77	34
6000	3	LSB-6000A-10	10	1	16 ⁹ / ₁₆	13 ³ / ₄	77	39
6000	3	LSB-6000A-15	15	1	16 ⁹ / ₁₆	13 ³ / ₄	77	44
6000	3	LSB-6000A-20	20	1	16 ⁹ / ₁₆	13 ³ / ₄	77	49
12000	6	LSB-12000A-5	5	2	22 ⁷ / ₁₆	13 ³ / ₄	84	64
12000	6	LSB-12000A-10	10	2	22 ⁷ / ₁₆	13 ³ / ₄	84	75
12000	6	LSB-12000A-15	15	2	22 ⁷ / ₁₆	13 ³ / ₄	84	86
12000	6	LSB-12000A-20	20	2	22 ⁷ / ₁₆	13 ³ / ₄	84	97

NOTE:
For complete dimensional data, refer to Coffing Dimensional Databook.

* Standard lifts shown. Other lifts available - Contact us